

	Duo	NV+	Duo v2	NV+ v2	Ultra 2	Ultra 2 Plus	Ultra 4	Ultra 4 Plus	Ultra 6	Ultra 6 Plus
硬件										
- CPU	IT3107	IT3107	Marvell 6282	Marvell 6282	Intel	Intel 双核	Intel	Intel 双核	Intel 双核	Intel 双核
- 内存	256 MB	256 MB	256 MB	256 MB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB
- 用于固件存放的内嵌 flash memory	64 MB	64 MB	128 MB	128 MB	128 MB	128 MB	128 MB	128 MB	128 MB	128 MB
- 外观	桌面型	桌面型	桌面型	桌面型	桌面型	桌面型	桌面型	桌面型	桌面型	桌面型
- Serial ATA 通道数	2	4	2	4	2	2	4	4	6	6
- 可热插拔硬盘架	√	√	√	√	√	√	√	√	√	√
- 可锁硬盘架	√	√	√	√						
- 10/100/1000 以太网接口	1	1	1	1	2	2	2	2	2	2
- USB 2.0 接口	3	3	1	1	2	2	3	3	3	3
- USB 3.0 接口			2	2	1	1				
- LCD/OLED 显示屏		LCD		LCD			LCD	LCD	OLED	OLED
- 兼容 SATA I & II HDD	√	√	√	√	√	√	√	√	√	√
- 原厂 SATA II 支持			√	√	√	√	√	√	√	√
- Kensington 锁	√	√	√	√	√	√	√	√	√	√
RAID										
- 自动扩展 X-RAID™	√	√								
- 自动扩展 X-RAID2™			√	√	√	√	√	√	√	√
- 支持双冗余的 X-RAID2™										
- 在线磁卷扩展		√	√	√	√	√	√	√	√	√
- RAID 级别 0/1 (Flex-RAID)	√	√	√	√	√	√	√	√	√	√
- RAID 级别 5 (Flex-RAID)		√		√			√	√	√	√
- RAID 级别 6 (Flex-RAID)									√	√
- JBOD 支持			√	√						
- 多磁卷支持 (Flex-RAID)	√	√	√	√	√	√	√	√	√	√
- 热插拔支持	√	√	√	√	√	√	√	√	√	√
- 热备盘支持 (Flex-RAID)		√			√	√	√	√	√	√
- 后台同步及智能同步接续	√	√	√	√	√	√	√	√	√	√
- 生命支持模式	√	√			√	√	√	√	√	√
磁卷										
- 磁卷管理		√			√	√	√	√	√	√
- 磁卷监控及资源查览			√	√						
- 单一磁卷自动扩展 (X-RAID/X-RAID2)	√	√	√	√	√	√	√	√	√	√
- 日志文件系统	√	√	√	√	√	√	√	√	√	√
- 计划排定的快照		√								
- 共享模式配额限制		√								
- 用户与群组配额限制	√	√			√	√	√	√	√	√
- 移植至 NV+/1100	√	√								
- 磁盘纠错					√	√	√	√	√	√
- 后台磁卷检查					√	√	√	√	√	√
- 可扩展的 iSCSI target					√	√	√	√	√	√

备份										
- 综合 Frontview™ 备份管理	√	√			√	√	√	√	√	√
- 综合 Dashboard 备份管理			√	√						
- 加速的 USB NTFS			√	√						
- 可执行按序排定任务的备份按钮	√	√	√	√	√	√	√	√	√	√
- 快照备份		√								
- CIFS/NFS/FTP/HTTP & rsync 协议备份	√	√	仅支持 CIFS	仅支持 CIFS	√	√	√	√	√	√
- 与 USB 移动硬盘的相互备份	√	√	√	√	√	√	√	√	√	√
- 内置的 Time Machine 支持	√	√	√	√	√	√	√	√	√	√
- 多台 ReadyNAS 设备间的同步	√	√			√	√	√	√	√	√
- 基于 rsync 的完整与增量备份	√	√	即将可用	即将可用	√	√	√	√	√	√
- 系统设置备份与还原		√			√	√	√	√	√	√
- 内置的 ReadyNAS Vault™ 支持	√	√	即将可用	即将可用	√	√	√	√	√	√
- 多系统克隆		√								
内含软件										
- Memeo Premium Backup Licenses (Windows)",	3	3	1	1	3	3	3	3	3	3
- ReadyNAS Photos	√	√								
- ReadyNAS Photos II			√	√	可选	可选	可选	可选	可选	可选
USB 设备支持										
- 移动硬盘及闪存	√	√	√	√	√	√	√	√	√	√
- 支持 FAT32, Ext2, Ext3 及 NTFS	√	√	√	√	√	√	√	√	√	√
- 数码相机	√	√	√	√	√	√	√	√	√	√
- 打印机	√	√	√	√	√	√	√	√	√	√
- UPS	√	√	√	√	√	√	√	√	√	√
Web 浏览器支持										
- Internet Explorer 8.0+	√	√	√	√	√	√	√	√	√	√
- Safari 4.0+	√	√	√	√	√	√	√	√	√	√
- Opera 11.0+	√	√	√	√	√	√	√	√	√	√
- Firefox 3.0+	√	√	√	√	√	√	√	√	√	√
- Chrome 8.0+	√	√	√	√	√	√	√	√	√	√
- iPad / iPhone			√	√						
- Android 2.3+			√	√						
语言										
- 管理界面：英文，德文，日文，中文，韩文， 法文，瑞典文，荷兰文，意大利文，西班牙文， 波兰文，俄文	√	√	√	√	√	√	√	√	√	√
- 文件名：Unicode	√	√	√	√	√	√	√	√	√	√
电气										
- 电源	外接的 60W	120W	外接的 60W	外接的 90W	外接的 60W	外接的 60W	120W	120W	300W	300W
- 输入：100-240V AC, 50/60 Hz	√	√	√	√	√	√	√	√	√	√
功耗										
- 典型情况下 (2 x 500GB for Duo 4 x 500GB for NV+, 2 x 1TB for Duo V2, 4 x 1TB for NV+ V2, 2/4/6 x 2TB for Ultra 2/4/6)	35W	55W	24.2W	48.4W	35W	35W	52W	52W	74W	82W
- 硬盘停转	√	√	√	√	√	√	√	√	√	√
- 定时开关机	√	√	√	√	√	√	√	√	√	√
- UPS 电池蓄电过低时自动关机	√	√			√	√	√	√	√	√
- 从网络唤醒			即将可用	即将可用	√	√	√	√	√	√

